



SAFETY DATA SHEET

SECTION 1 IDENTIFICATION -

Identifier: RESURFACER, RESURFACER XLR8

Mineral filled, Emulsified Asphalt Sealcoat Material

Other Identifiers: Anionic Sealcoat material

Manufacturers Name: Special Asphalt Products, Inc.

Address: 3484 Old Salem Rd NE Albany, OR 97321

Emergency phone # 800-535-5053 (Infotrac)

Other Information Calls: 800-953-6490 Product Information

Revision Date Dec 12, 2017

SECTION 2 HAZARD IDENTIFICATION

Classification: Carcinogenicity, Category 2

Label Elements

Hazard

Symbol:



Hazard Statement:

Can cause Eye irritation.

Can cause skin irritation.

May cause respiratory irritation

Precautionary Statement

Avoid breathing fumes and vapors.

Wash hands and skin if it comes in contact.

Wear protective gloves, clothing, eye, and face protection.

Hazards from Exposure.

Acute

EYES

May cause eye irritation or redness.

SKIN

Contact may cause skin irritation.

INHALATION

Dust from cured coating may provoke asthmatic response in persons with asthma or those who are sensitive to airway irritants.

INGESTION

If swallowed may cause nausea, diarrhea and vomiting.

CHRONIC

Long term exposure to asphalt fumes may cause bronchitis.

SECTION 3 COMPOSITION AND INFORMATION OF INGREDIENTS

INGREDIENTS	CAS. NO.	WT %	OSHA PEL	STEL	ACGIH TLV	
Petroleum Asphalt	8052-42-4	>100%	NE		5 mgm3	
Water	7732-18-5	25 % - 75%				
Emulsifiers	Proprietary	.1 - 6%				
May Contain one or all of the following.						
Proprietary Distillate	proprietary	0-25%	NE		NE	
Polymer	proprietary	0 -8%	NE		NE	
Proprietary Additives	proprietary	0-5%	NE		NE	
Hydrogen Sulfide	.7783-06-4	<0.1%	10ppm	15ppm	10ppm	

Additional Comments:

Though Further Detail On Contents May Be Confidential, All Pertinent Hazards Are Addressed In This SDS.

SECTION 4 FIRST AID MEASURES

INHILATION :If respiratory system develop remove individual to fresh air and keep comfortable.

If breathing remains difficult seek immediate medical attention.

SKIN CONTACT: In the event of skin contact wash with soap and water.

EYE CONTACT: If redness or irritation develops from exposure to fumes, remove individual to fresh air.

Flush eyes with cold water if symptoms continue, seek medical attention.

If contact is made with product flush eyes with cold water for 15 minutes and seek immediate medical attention.

INGESTION: If product is swallowed, rinse mouth with water and seek medical attention. Do not induce vomiting.

NOTE TO PHYSICIANS: Asphalt is not harmful to the skin. It will detach after a few days.

If it has to be removed use only medical approved solvents.

Most symptoms are acute and can be delayed. These include but are not limited too irritation, redness, swelling, pain, nausea, and blurred vision.

SECTION 5 - FIRE-FIGHTING MEASURES.

Flash Point: Not Classified as a Flammable or Cumbustable material.

Flammable limits in air % by volume: N/D

Extinguisher Media: Dry Chemical, CO₂, Halon, Water Spray, or standard foam.

Fire Fighting Procedures:

Move containers from fire area if possible. Cool fire-exposed containers with water from side until well after fire is out. Stay away from storage tank end for massive fire in storage area. Use unmanned hose holder or monitor. Use flooding amounts of water as a fog, as solid streams may cause eruptions. Withdraw immediately in case of rising sound from venting safety device or any discoloration of storage vessel due to fire. Extinguish only if flow can be stopped. Water or foam may cause frothing. Avoid breathing toxic vapors and keep upwind.

Protective Equipment

Structural Firefighters should where Self Contained Breathing Apparatus to protect from Corrosive and Toxic vapors. Hydrogen sulfide is heavier than air and will collect in low lying areas.

ADDITIONAL COMMENTS: Represents a slight fire hazard when exposed to heat or flame.

NFPA RATING SYSTEM

Flammability



SECTION 6 ACCIDENTAL RELEASE

Personal Precautions, Protective equipment, and Emergency Procedures.

Personal Precaution

Avoid all contact with spilled or released material. Use PPE recommended in section 8

Notify Fire Department and other appropriate Federal, State, and local agencies.

Protective Equipment.

An Emergency wash station to flush eyes as well as body.

Emergency Procedures.

Shut off area ignition sources. Stop leak if it can be done without risk.

For spills, use absorbent material and place into container.

Dike ahead of large spill for later disposal. Prohibit smoking in affected area.

Isolate area and restrict entry.

Containment and Cleanup.

Stop spill or release if it can be completed safely. Material will flow, Keep material from flowing into storm drains, sewers, and water ways by covering or diking. Contact the appropriate agency should spilled material get into waterways.

Follow appropriate procedure and guidelines to clean up and dispose of spilled material. Dispose of material by Federal, State, and Local Guidelines.

SECTION 7 Handling and Storage.

Handling

Review section 8 for proper PPE before handling product, it is stored and transported at Temperatures between 32°F and 150°F. Thermal burns are a hazard. Do not eat, drink, smoke, or apply make up while handling material. Wash with soap and water after coming in contact with material.

Avoid breathing vapors or mist generated by products.

Storage.

Product is usually stored between 32°F and 150°F. Do not use, or store near heat, sparks, or open flames. Hydrogen sulfide maybe present in empty tanks, or transport vessels. Follow confined space entry guidelines if you must enter one of these containers.

Section 8 Exposure Controls/ Personal Protection.

Exposure Limits.

Component	ACGIH	OSHA
Asphalt Cas # 8052-42-4	.5 mg/m ³ TWA	No PEL Established
Hydrogen Sulfide CAS # 7783-06-4	1PPM TWA 5PPM STEL	20 PPM Ceiling

TWA- Time weighted Average

PEL-m Permissible Exposure Limit.

STEL- Short Term Exposure Limit

Engineering Controls

Ensure ventilation equipment can maintain airborne vapor levels below limits listed above.

Personal Protective Equipment. (PPE)

Eye and Face Protection. Wear eye protection and face shield meeting US OSHA 29CFR 1910.133 to protect eyes and face from hot material.

Respiratory Protection. Airborne concentrations need to be maintained below levels listed above. If not, a NIOSH approved air-purifying respirator, with an Organic Vapor cartridge, or a Self Contained breathing apparatus must be used if oxygen concentrations are low.

Hand Protection. Use chemical resistant gloves to protect skin from repeated or prolonged contact.

Body Protection. Wear approved respirator, gloves, hat, shoes and long sleeved clothing to prevent contact with material.

Personal Hygiene. Do not eat or drink when handling material. Emergency eye wash and Shower Station should be available to cool material if it come in contact with the employee.

Section 9 Physical and Chemical Properties.

Appearance and Odor:	Brown to Black viscous liquid with mild asphalt odor.
Odor Threshold:	Not Available.
Physical State:	Semi Solid at Room Temperature, Viscous Liquid at elevated Temperatures.
Vapor Pressure	NA
Vapor Density	NA
pH	7.5 - 13.0
Relative Density	NA
Solubility	Completely Soluble
Flash Point	None
Evaporation Rate	Equal to water
Flammability	Not Available.
Partition Coefficient	Not Available.
Auto-Ignition Temp	Not Available.
Decomposition Temp:	Not Available.
Softening Point	Not Available.
Viscosity	Not Available.

Section 10 Stability and Reactivity.

Reactivity Exposure to extreme heat, sources of ignition, and incompatible materials.

Chemical Stability Stable under normal storage conditions.

Hazardous Polymerization Will not Occur.

Incompatible Materials Oxidizers, Acids, and Bases.

Decomposition Hot material may produce Hydrogen Sulfide.

Section 11 Toxicological Information

Possible Exposure Routes Inhalation, Ingestion, Eye Contact, and Skin Contact.

Acute Exposure Toxicity.

Oral:	Not Available
Dermal:	Not Available
Inhalation:	Not Available

Component Toxicity

Component	CAS #	LD50 Oral	LD50 Dermal	LC 50
Asphalt	8052-42-4	Not Available	Not Available	Not Available
Hydrogen Sulfide	7783-06-4	Not Available	Not Available	440 ppm (Rat)

Target Organs: Eyes, Lungs, Skin, Respiratory System, Blood, Central nervous system

Symptoms

Inhalation Included but not limited to cough, sneezing, nasal discharge, headache, nose, and throat pain. With

trace amounts of Hydrogen Sulfide it will produce a rotten egg smell at very low concentrations, 1-5 PPM. As the concentration increases loss of smell, headache, dizziness, nausea, vomiting, and irritation of respiratory tract. Death will occur at concentration of 300 to 450ppm and 1 to 3 hours of exposure.

Eye May cause eye irritation.

Skin May cause skin irritation.

Ingestion May cause nausea, vomiting, diarrhea, constipation, severe abdominal pain

Skin Sensitization: Not Available.

Respiratory Sensitization: Not Available.

Medical Conditions Not Available.

Chronic Effects

Target Organs: Eyes, Lungs, Skin, Respiratory System, Blood, Central nervous system

Chronic Effects: Continuous contact may cause skin irritation, redness, and swelling. Hydrogen Sulfide can cause headaches, nausea, vomiting, eye and nasal irritation, and damage to the respiratory system.

Carcinogenicity: There has not been evidence presented by the National Toxicology Program or Occupational Safety and Health Administration that establishes Asphalts a carcinogen.

Section 12 Ecological Information.

Toxicity Not Available.

Persist or Degrade. Product has a very low rate of biodegradation.

Bioaccumulation It is unlikely due to low water solubility.

Environmental movement: Not Available.

Adverse Effects: There is not any evidence available that shows the product effect on Aquatic Life, However, Latex a possible ingredient is harmful to Aquatic Life.

Section 13 Disposal Considerations.

Instructions Dispose of material in according to Federal, State, and local regulations. Must comply with the most stringent guidelines.

Section 14 Transportation Information.

All Grades Transportation.

D.O.T. PROPER SHIPPING NAME (49 CFR 172.101):

Non- Regulated Material

D.O.T. HAZARD CLASS (49 CFR 172.101):

None

UN / NA CODE (49 172.101):

None

PACKAGING GROUP (49 172.101):

None

BILL OF LADING DESCRIPTION (49 172.101):

None - labeled as emulsified Asphalt

D.O.T. LABELS REQUIRED (49 172.101):

None

D.O.T. PLACARDS REQUIRED (49 172.101):

None

Section 15 Regulatory Information.

US Regulations

SARA Reporting: Product is not subject to the reporting requirements of Section 302, 304, and 313 of Title III of the Superfund Amendments Reauthorization Act.

TSCA: All components in this product are listed on the US Toxic Substance Control Act.

SARA 311/312

Acute Health: Yes

Chronic Health: Yes

Fire: No

Reactivity: NO

Threshold Planning Quantities:

No Specific Threshold Planning Quantities for product.

State Regulations

California:

Product contains substances known to the State of California to cause Cancer, Birth Defects, or Reproductive harm.

Section 16 Other Information.

Disclaimer:

The information in this document applies to the specific material as it is supplied. If the material is used in combination with another material the document may not apply. The user has the responsibility to satisfy oneself on the usability of the information supplied in this document, and assumes the risk thereof.

Date of SDS

12/10/2017

Prepared by

Special Asphalt Products